

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C07C 227/02, 229/16	A1	(11) International Publication Number: WO 00/66539
		(43) International Publication Date: 9 November 2000 (09.11.00)
<p>(21) International Application Number: PCT/US00/12023</p> <p>(22) International Filing Date: 2 May 2000 (02.05.00)</p> <p>(30) Priority Data: 60/132,261 3 May 1999 (03.05.99) US</p> <p>(71) Applicant (for all designated States except US): MONSANTO CO. [US/US]; 800 N. Lindbergh Blvd., St. Louis, MO 63167 (US).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): FRANCZYK, Thaddeus, S., II [US/US]; 2174 Terrimill Terrace, Chesterfield, MO 63017 (US). MOENCH, William, L., Jr. [US/US]; 6 West Point Lane, Town & Country, MO 63131 (US).</p> <p>(74) Agent: FINKELSTEIN, Ira, D.; Howrey Simon Arnold & White, LLP, 750 Bering Drive, Houston, TX 77057-2198 (US).</p>		<p>(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>
(54) Title: PROCESS FOR THE PREPARATION OF CARBOXYLIC ACID SALTS FROM PRIMARY ALCOHOLS		
<p>(57) Abstract</p> <p>The present invention provides a new and useful improvement in the process to manufacture a carboxylic acid salt, particularly an amino carboxylic acid salt, from a primary alcohol, particularly a primary aminoalcohol. The process of manufacturing amino carboxylic acid salts comprises contacting an aqueous solution of a primary aminoalcohol with a strong hydroxide base selected from the group consisting of an alkali metal hydroxide, an alkaline earth metal hydroxide, an ammonium hydroxide compound including a tetraalkyl ammonium hydroxide, or the like, in the presence of an effective amount of a catalyst. The catalyst comprises one or more of elements selected from the group consisting of copper, cobalt, nickel, and cadmium as well as optionally lesser amounts of chromium, titanium, niobium, tantalum, zirconium, vanadium, molybdenum, manganese, tungsten, cobalt, nickel, or mixtures thereof. The reaction mixture contains less than about 3000 ppm, preferably less than about 500 ppm, more preferably less than about 100 ppm of oxidized copper (Cu⁺ and/or Cu²⁺) during the reaction. The concentration of oxidizing agents in the reactants is minimized to prevent formation of oxidized copper from metallic copper catalyst.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BF	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NR	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	VU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

WO 00/66539

PCT/US00/12023

PROCESS FOR THE PREPARATION OF CARBOXYLIC ACID SALTS FROM PRIMARY ALCOHOLS

BACKGROUND OF THE INVENTION

1. FIELD OF THE INVENTION

5 This invention relates to the preparation of carboxylic acid salts, and more particularly, to a method for the preparation of amino carboxylic acid salts by the reaction of primary aminoalcohols with a hydroxide base in the presence of a catalyst.

2. DESCRIPTION OF RELATED ART

10 Carboxylic acid salts are useful in various applications. The salts can be neutralized to the corresponding acid which is also useful in a number of applications, such as a raw material for pharmaceuticals, agricultural chemicals, pesticides and the like. Many of such carboxylic acids are available commercially in large quantities.

15 Copper catalysts are known to be effective for the conversion of primary alcohols to carboxylic acid salts (Chirwood 1945) and, particularly, alkanolamines to aminocarboxylic acids (Goto et al. 1988). The prior art maintains that both metallic copper and copper salts or oxides (Cu^+ , Cu^{2+} , or both) are suitable catalysts to facilitate this conversion.

20 A journal article "Structure and Activity of Chromium-Promoted Raney Copper Catalyst for Carbon Monoxide Oxidation" by Laine et al., Applied Catalysis, 44 (1-2), pages 11-22, discloses that chromium-promoted Raney copper catalysts were prepared, and their activity for the oxidation of carbon monoxide was measured. The surface area of the Raney copper catalyst was directly related to the aluminum content in the precursor alloy and to a lesser extent to the presence of chromium. Bulk cuprous oxide and cupric oxide were detected by x-ray diffraction in the Raney copper catalyst. The presence of chromium inhibited the formation of cupric oxide but not of cuprous oxide. The activity decreased as chromium content increased.

25 U.S. Patent No. 4,782,183 to Goto et al. describes a method for the manufacture of amino carboxylic acid salts which comprises contacting an aminoalcohol with an alkali metal hydroxide in the presence of a Raney copper catalyst, or a copper catalyst supported on zirconium oxide. The catalyst can also be an inorganic or organic salt of copper, or an oxidized surface of a metallic copper that is then reduced with hydrogen.

30 U.S. Patent No. 4,810,426 to Fields et al. describes a process for the production of N-phosphonomethylglycine by oxidizing N-phosphonomethylethanolamine, or the cyclic internal ester thereof, with an excess of an aqueous alkali and a copper catalyst, and thereafter, heating at

WO 00/66539

PCT/US00/12023

- 2 -

a temperature between 200°C and 300°C. The catalyst is selected from cadmium, zinc, copper, palladium, platinum, and their respective oxides, hydroxides, and salts.

U.S. Patent No. 5,220,054 to Urano et al. describes a method for the manufacture of amino carboxylic acid by the oxidative dehydrogenation reaction in the presence of an alkali metal hydroxide, a copper containing catalyst, and water characterized by maintaining the nickel concentration below 40 ppm.

U.S. Patent No. 5,292,936 to Franczyk describes an improved process to prepare an amino carboxylic acid salt. According to the process an aqueous solution of an aminoalcohol is contacted with an alkali metal hydroxide in the presence of an effective amount of a Raney copper catalyst that has from about 50 parts per million to about 10,000 parts per million of an element selected from the group consisting of chromium, titanium, niobium, tantalum, zirconium, vanadium, molybdenum, manganese, tungsten, cobalt, nickel and mixtures thereof.

Although satisfactory results are achieved by the processes of the prior art to convert an alcohol to a carboxylate using a copper catalyst, or even a Raney copper catalyst, it has now been found, in accordance with the teachings of the present invention, that the process of the present invention can convert an alcohol to an acid salt with greater conversion. This increase in yield and selectivity results in significant capital savings and operating costs when such reactions are practiced on a commercial scale.

SUMMARY OF THE INVENTION

The present invention provides a new and useful improvement in the process to manufacture a carboxylic acid salt, particularly an amino carboxylic acid salt, from a primary alcohol, particularly a primary aminoalcohol.

The process of manufacturing amino carboxylic acids salts comprises contacting an aqueous solution of a primary aminoalcohol with a strong hydroxide base selected from the group consisting of an alkali metal hydroxide, an alkaline earth metal hydroxide, an ammonium hydroxide compound including a tetraalkyl ammonium hydroxide, or the like, to form a reaction mixture, in the presence of an effective amount of a catalyst. The primary aminoalcohol and the strong hydroxide base react in the reaction mixture to form an amino carboxylic acid salt. The catalyst comprises one or more of elements selected from the group consisting of copper, cobalt, nickel, and cadmium as well as optionally lesser amounts of chromium, titanium, niobium,

WO 00/66539

PCT/US00/12023

- 3 -

tantalum, zirconium, vanadium, molybdenum, manganese, tungsten, cobalt, nickel, and mixtures thereof.

The reaction mixture contains less than about 3000 ppm, preferably less than about 500 ppm, more preferably less than about 100 ppm of oxidized copper either in soluble, complexed, colloidal, or particulate form during the reaction. The copper containing catalyst contains less than 50 ppm by weight, preferably less than 10 ppm by weight, more preferably less than 1 ppm by weight, of oxidized copper compared to the weight of active catalyst prior to starting the reaction. Examples of oxidized copper include cupric and cuprous ions, copper oxides, copper hydroxides, and the like. The presence of oxidized copper leads to poorer catalytic selectivity and activity.

The concentration of oxidizing agents in the reactants is minimized to prevent formation of oxidized copper from metallic copper catalyst. The concentration of oxidizing agents in the feedstocks and in the reaction mixture is preferably less than about 1000 ppm total, more preferably less than about 500 ppm total, even more preferably less than about 200 ppm total, and most preferably less than about 40 ppm.

DETAILED DESCRIPTION OF THE INVENTION

The present invention provides a new and useful improvement in the process to manufacture a carboxylic acid salt from a primary alcohol. More particularly, the present invention provides a new and useful improvement in the process to manufacture an amino carboxylic acid salt from a primary aminoalcohol.

The primary alcohols which are useful as starting materials in the process of the present invention can be monohydric or polyhydric, and also aliphatic, cyclic or aromatic compounds, including polyether glycols, which react with a strong base to form a carboxylate. It is necessary that the alcohol and the resulting carboxylate are stable in the strongly caustic mixture, and that the alcohol is somewhat water soluble.


Suitable primary monohydric alcohols include aliphatic alcohols which can be branched, straight-chain, or cyclic, and aromatic alcohols such as benzyl alcohol. The alcohols can be substituted with various non-hindering groups, provided that these substituent groups do not react with the hydroxide base or the catalyst at the temperatures and pressures for the conversion of the alcohol to the acid. Suitable aliphatic alcohols include ethanol, propanol, butanol, pentanol, and the like.

WO 00/66539

PCT/US00/12023

- 4 -

Aminoalcohols represented by the formula



are also useful as starting materials in the present process where n is from 2 to about 20. When R¹ and R² are both hydrogen and n is 2, the aminoalcohol is monoethanolamine. When one of R¹ and R² is -CH₂CH₂OH or -CH₂COOH, and the other R group is hydrogen and n is 2, the resulting product from the aminoalcohol is an iminodiacetate salt. When both R¹ and R² are -CH₂CH₂OH or -CH₂COOH, the resulting product from the aminoalcohol is a nitrilotriacetate salt. Specific aminoalcohols include, for example, n-hydroxyethylglycine acid, monoethanolamine, diethanolamine, triethanolamine, N-methylethanolamine, N-ethylethanolamine, N-isopropylethanolamine, N-butylethanolamine, N-nonylethanolamine, N-(2-aminoethyl) ethanolamine, N-(3-aminopropyl) ethanolamine, N,N-dimethylethanolamine, N,N-diethylethanolamine, N,N-dibutyl-ethanolamine, N-methyldiethanolamine, N-ethyldiethanolamine, N-propyldiethanolamine, N-butyldiethanolamine, N-methyl-N-(3-aminopropyl) ethanolamine, 3-amino-propanol, and salts thereof.

In the above formula, R¹ and/or R² can also be an alkyl group having from 1 to 6 carbon atoms, for example, methyl, ethyl, propyl, isopropyl, butyl, isobutyl and the like. There would then be provided corresponding amino acids with these alkyl groups which would be useful in a number of applications. R¹ or R² can also be a phosphonomethyl group such that the starting amino acid would be N-phosphonomethylethanolamine, and the resulting amino acid salt would be the salt of N-phosphonomethylglycine. If one of R¹ or R² were phosphonomethyl, and the other were -CH₂CH₂OH, the resulting amino acid salt would be the salt of N-phosphonomethyliminodiacetic acid, which can be converted to N-phosphonomethylglycine by any number of techniques known to those skilled in the art. If one of R¹ or R² were phosphonomethyl, and the other were a lower alkyl group, the resulting amino acid salt would be an N-alkyl-N-phosphonomethylglycinate which could be converted to N-phosphonomethylglycine by the teachings in U.S. Patent 5,068,404 to Miller and Balthazor, which is incorporated by reference herein.

A commercially important embodiment is where the aminoalcohol is diethanolamine, the strong hydroxide base is sodium hydroxide, the catalyst is comprised of Raney copper or

WO 00/66539

PCT/US00/12023

- 5 -

metallic copper on an inert support, and the amino carboxylic acid salt product is disodium iminodiacetate.

Manufacturing carboxylic acids salts comprises contacting an aqueous solution of a primary alcohol with a strong hydroxide base. The hydroxide base suitable for use in the process of the present invention include the alkaline earth metal hydroxide, such as magnesium hydroxide, calcium hydroxide, barium hydroxide and the like. The hydroxide base can also be a tetraalkyl ammonium hydroxide having up to 5 carbon atoms in each alkyl group, such as tetramethyl ammonium hydroxide, dimethyldipropyl ammonium hydroxide, tributylethyl ammonium hydroxide and the like. The hydroxide base may be other ammonium compounds. However, alkali metal hydroxides are preferred. Suitable alkali metal hydroxides for use in the process of the present invention include lithium hydroxide, sodium hydroxide, potassium hydroxide, rubidium hydroxide and cesium hydroxide. Because of their ready availability and ease of handling, sodium hydroxide and potassium hydroxide are preferred, and sodium hydroxide is especially preferred. The amount of the hydroxide base to be used is an equivalent amount in the range of about 1 to about 2 equivalents relative to the hydroxyl group of the alcohol to be used in the reaction. The hydroxide can be in any convenient form, for example flakes, powder, pellets or an aqueous solution.

Manufacturing carboxylic acids salts comprises contacting an aqueous solution of a primary alcohol with a strong hydroxide base in the presence of an effective amount of a catalyst.

The preferred catalyst contains metallic copper. One catalyst useful in this invention consists essentially of a hydroxide-resistant support; an anchor metal selected from the group consisting of platinum, palladium, ruthenium, silver, gold, and mixtures thereof deposited on the support; and an element selected from the group consisting of copper, cobalt, nickel, cadmium, and mixtures thereof on or combined with the anchor metal. The catalyst may contain other heavy metals as described in U.S. Patent No. 5,292,936, whose disclosure is incorporated herein by reference. These other heavy metals include chromium, titanium, niobium, tantalum, zirconium, vanadium, molybdenum, manganese, tungsten, cobalt, nickel and mixtures thereof.

The catalyst composition may be any catalyst known or developed by one in the art provided the limits on oxidized copper are met. The method of making the catalyst may be any method known to the art, for example, by electroless metal deposition as described in U.S. Patent No. 5,627,125, or by the process described in U.S. Patent No. 5,689,000, the disclosures

WO 00/66539

PCT/US00/12023

- 6 -

of which are incorporated herein by reference. Electroless metal deposition refers to the chemical deposition of an adherent metal coating on a suitable substrate in the absence of an external electric source. The anchor metal deposited on the hydroxide-resistant support can be a noble metal, for example silver, gold, platinum, palladium or ruthenium or mixtures thereof.

5 Platinum is preferred. A mixture may include an alloy comprising at least two noble metals, or may include two or more noble metals added sequentially to the hydroxide-resistant support.

The hydroxide-resistant support in the catalyst is necessary since the reaction to convert the alcohol to the corresponding acid salt is conducted in a strong basic solution. Suitable supports include titanium oxide, zirconium oxide and carbon. Carbon is preferred. Suitable
10 hydroxide-resistant supports containing a suitable anchor metal can be obtained commercially.

Alternatively, another catalyst useful for the present invention is a Raney copper catalyst that may contain lesser amounts of chromium, titanium, niobium, tantalum, zirconium, vanadium, molybdenum, manganese, tungsten, cobalt, nickel and mixtures thereof.

The amount of catalyst to be used to convert the alcohol to the corresponding acid can
15 range between about 1% and about 70% by weight, preferably 1 to 40% by weight, based on the amount of the starting alcohol.

The presence of oxidized copper leads to poorer catalytic selectivity and activity. This finding was unexpected based upon the prior art that purports that excellent yields of aminoacids can be obtained when oxidants such as oxygen are introduced into the reaction mixture.

20 It is advantageous to maintain the amount of oxidized copper (Cu^+ and/or Cu^{2+}) in the reaction mixture to below about 3000 ppm, preferably below about 500 ppm, more preferably below about 100 ppm, and most preferably below about 50 ppm.

The term "oxidized copper" includes cupric and cuprous ions, copper oxides, copper hydroxides, or other copper salts, wherein the oxidized copper is exposed or available to the
25 fluids, and wherein the oxidized copper is in the form of either particulate, colloidal, complexed, or soluble form.

The term "particulate form" includes oxidized copper attached to or embedded in, the catalyst, so long as the oxidized can contact fluid.

The term "reaction mixture" is defined as the totality of material that takes part in the
30 reaction, i.e., the alcohol, the base, the solvents, the catalyst that is exposed to the fluids, the gas charged to the reactor, and any other adjuvants.

WO 00/66539

PCT/US00/12023

- 7 -

It is also desirable to treat the copper containing catalyst to ensure that the catalyst has essentially no, i.e., less than 500 ppm by weight, preferably less than 100 ppm by weight, more preferably less than 40 ppm by weight, of oxidized copper compared to the weight of catalyst prior to starting the reaction.

5 As used herein the term "catalyst" includes the material exposed to the fluids, but not any inert material or material not exposed to fluids. For example, a completely reduced copper plating completely surrounding a particle of copper oxide, so that the copper oxide is not exposed to the fluid, would contain for purposes of this disclosure no oxidized copper.

The reaction mixture contains less than about 3000 ppm, preferably less than about 1000
10 ppm, of oxidized copper either in soluble, complexed, colloidal, or particulate form both before and during the reaction. It is more preferred that the reaction mixture contains less than about 100 ppm, and most preferably less than about 50 ppm, of oxidized copper either in soluble, complexed, colloidal, or particulate form before and during the reaction.

The amount of oxidized copper may increase at the start of the reaction, as oxidizing
15 agents present in the reaction mixture contact and react with the catalyst. The reaction environment is highly reducing, however, and it is recognized by those skilled in the art that the concentration of oxidized copper in the reaction mixture will thereafter generally decline over time.

Oxidized copper can originate from, for example, poorly reduced or oxidized copper
20 catalysts or by the introduction of oxidizing agents such as molecular oxygen, ozone, and salts of chlorates, chlorites, hypochlorites, and perchlorates. The presence of these oxidizing agents can oxidize some of the catalyst, forming cupric or cuprous ions.

The quantity of oxidized copper can be reduced in a number of ways. First, it may be possible to reduce the dissolved molecular oxygen concentration in the reaction mixture. The
25 concentration of dissolved molecular oxygen in the mixture is advantageously less than about 5 ppm, more preferably less than about 1 ppm, and even more preferably less than about 0.5 ppm.

This can be done with sequestering agents or by other techniques known to the art. Preventing oxygen from contacting a copper catalyst is one method. This can be done by keeping the catalyst under a fluid, for example under water.

30 Simple exclusion of air from the reactor, and of de-aerating feedstocks, i.e., the primary alcohol and the strong hydroxide base, by vacuum or by inert gas purge, will reduce the amount of oxygen in the reaction mixture. Air can be removed from a reactor by displacement with

WO 00/66539

PCT/US00/12023

- 8 -

fluids, by displacement with another gas, by vacuum, or by a combination thereof. Oxygen can be purged from the mixture, or from individual feedstocks, by bubbling through the mixture a gas containing little oxygen, such as nitrogen or hydrogen.

Oxygen scavengers can be added to the mixture, or to one or more feedstocks, to reduce dissolved oxygen. Examples of oxygen scavengers include sulfites such as sodium sulfite. An effective amount of an oxygen scavenger is generally between about 5 ppm to about 50 ppm.

Other oxygenating agents, such as chlorite, chlorate, perchlorate, and hypochlorite salts, can be excluded from the reaction mixture by a variety of methods. First, feedstocks may be selected that contain little of the above oxidizing agents. Commercial hydroxide solutions can contain between 100 and 5000 ppm oxidizing agents. One mole of sodium chlorate, for example, can theoretically generate three to six moles of oxidized copper from the catalyst. Sodium hydroxide, the lowest-cost alkali hydroxide used for the conversion of aminoalcohols to aminocarboxylic acid salts, is often commercially produced by electrolysis of NaCl solutions. This process co-produces varying amounts of chlorine oxides, chiefly in the form of sodium chlorate (NaClO₃). Use of sodium hydroxide containing sodium chlorate results in poorer selectivity in the conversion of aminoalcohols.

While not being bound to any theory, it is believed these oxidizing agents oxidize the copper-containing catalyst. Said catalyst may well be reduced, or partially reduced, during the course of the reaction.

Quantities of oxidizing agents and of oxidized copper in feedstocks and in the reaction mixture can be eliminated by exposure to a reducing agent, for example, a metal hydride, sodium borohydride, formaldehyde, molecular hydrogen, hydrazine, formic acid or salt thereof. The concentration of these oxidizing agents in both the feedstocks and in the reaction mixture is preferably less than about 1000 ppm total, more preferably less than about 500 ppm total, even more preferably less than about 200 ppm total, and most preferably less than about 40 ppm. The amount of reducing agent added should be at least sufficient to reduce the concentration of oxidizing agents to below that level. An excess is preferred. The absolute amount of reducing agents will depend on the concentration of oxidizing agents in the feedstock.

It is preferred that the concentration of these oxidizing reagents be reduced prior to exposing the various feeds, including the primary alcohol and the strong hydroxide base, to the catalyst.

WO 00/66539

PCT/US00/12023

- 9 -

Oxidized copper ions may be removed from the system. An effective quantity of acid or chelating acid may typically be between about 500 ppm and about 5000 ppm. The oxidized copper or other metal ions also may be removed from the reaction mixture, or from the separate feedstocks, by known means, for example by exposing the reaction mixture or the feedstocks to ion exchange resins.

Finally, the presence of oxidized copper on the surface of the catalyst prior to introduction of the fluid feedstocks has been found to be a source of oxidized copper.

The copper ions on a catalyst may be removed by washing the catalyst with an acid, for example, an organic acid or an inorganic acid, or with a chelating acid, for example, EDTA. The washing may effectively remove the copper ions from the catalytic agent, and the washing fluid can be withdrawn before introduction. An effective quantity of acid or chelating acid may typically be between about 10 ppm and about 5000 ppm. Use of deaerated fluids for washing and rinsing, that may optionally contain oxygen scavengers, will help prevent formation of additional oxidized copper.

The catalyst may be pretreated with a reducing agent, for example, a metal hydride, sodium borohydride, formaldehyde, molecular hydrogen, hydrazine, formic acid or salt thereof. While these compounds may also be added to the feedstock, it may be desirable to treat the catalyst with these agents before introducing the liquid feeds. Said reducing agents may be contacted with the catalyst as a fluid, a vapor, or a gas. The expedient of charging the reactor with hydrogen gas will reduce oxidized copper on the catalyst.

In the process of the present invention, it is necessary to contact the alcohol with an alkali metal hydroxide in the presence of the catalyst of the present invention at a temperature between about 100°C and 220°C, preferably between about 140°C and about 160°C. At temperatures above about 220°C, the catalyst begins to lose selectivity. At temperatures below about 100°C, satisfactory results can be obtained, but the reaction is slow.

Pressure is required for the reaction to proceed at the temperatures indicated above. However, the reaction pressure is desired to be as low as possible to insure high reaction velocity. Generally, it is necessary to exceed the minimum pressure at which the reaction proceeds in the liquid phase, preferably between about 1.96×10^5 pascals and about 2.94×10^6 pascals (about 2 and about 30 kg/cm²), preferably in the range of about 4.90×10^5 pascals and about 1.96×10^6 pascals (about 5 to 20 kg/cm²). The conversion of the alcohol to the

WO 00/66539

PCT/US00/12023

- 10 -

corresponding salt of the acid proceeds with the liberation of hydrogen, which should be vented with care from the reaction vessel.

The invention is further illustrated by but not limited to the following examples.

Example 1

5 This comparative example started with only oxidized copper as the catalyst. Diethanolamine (18.86 g, 0.1794 mole), aqueous sodium hydroxide (50 wt%, 30.37 g, 0.380 mole), cupric oxide (3.95 g, 0.0497 mole), and water (28.9 g) were charged to a 0.160 liter nickel autoclave. The reactor was purged with nitrogen and pressurized to 135 psig with nitrogen before heating the mechanically stirred mixture to 160°C for 12.6 hours while venting
10 gas in excess of 135 psig. This procedure eliminated air in the reactor, which is a source of dissolved oxygen. The oxidized copper content of the reaction mixture was about 38,500 ppm by weight. After filtration of the catalyst, analysis of the product mixture revealed 78.2 mole percent iminodiacetate, 8.8 mole percent hydroxyethylglycine (HEG), a product of incomplete conversion, and 9.7 mole percent glycine by-product based on the initial charge of
15 diethanolamine. The presence of glycine indicates the catalyst is less selective in promoting the desired reaction to form glyphosate. The quantity of glycine is therefore used to evaluate catalyst selectivity, with lower quantities of glycine being evidence of greater catalyst selectivity.

Example 2

20 An essentially identical reaction as described in Example 1, except with reduced metallic copper (Raney copper) in place of cupric oxide, requires 4.2 hours to produce a reaction product that is 93.9 mole percent iminodiacetate, 1.1 mole percent HEG, and 1.6 mole percent glycine. The oxidized copper in the reaction mixture in Example 1 gave six times more glycine than the reaction with reduced copper.

25 Example 3

Diethanolamine (62.71 g, 0.5964 mole), aqueous sodium hydroxide (50 wt%, 101.60 g, 1.270 mole), water (72.5 g), and metallic copper catalyst (Raney copper, 12.84 g, 0.02021 mole) were charged to a 300 ml nickel autoclave equipped with a mechanical stirrer. The vessel was purged with nitrogen and pressurized to 135 psig with nitrogen. This eliminated a source of
30 oxygen. After 2.7 hours of heating at 160° C all hydrogen evolution had essentially ceased and the reactor was cooled. Analysis of the product mixture after careful filtration of the catalyst to

WO 00/66539

PCT/US00/12023

- 11 -

avoid air exposure yielded a iminodiacetate product mixture containing 0.69 mole percent glycine.

Example 4

Reuse of the catalyst of Example 3 in a subsequent reaction under conditions essentially
5 identical to those in Example 3 yielded an iminodiacetate product mixture that contained 0.79 mole percent glycine after 3.5 hours.

Example 5

Identical reactions to those described in Example 3 above were performed with the exception that the reactor was prepressurized to 100 psig with air instead of nitrogen. Oxygen
10 was not excluded from the reaction mixture. The oxygen concentration in the reaction mixture was about 5 ppm. Analysis of the iminodiacetate product mixtures revealed it contained 0.88 mole percent glycine.

Example 6

Identical reactions to those described in Example 4 above were performed with the
15 exception that the reactor was prepressurized to 100 psig with air instead of nitrogen. The oxygen concentration in the reaction mixture was about 5 ppm. Analysis of the iminodiacetate product mixtures revealed it contained 0.94 mole percent glycine.

Example 7

Four tests were run to determine the effect of oxidizing agents in the reaction mixture on
20 catalyst selectivity

The catalyst was weighed out in water in a tared graduated cylinder. The catalyst was transferred to a 300 ml nickel reactor equipped with a stirrer. For a typical recycle reaction, the nickel vessel was charged with diethanolamine (62.5 grams, 0.59 mole), an aqueous solution of purified-grade NaOH (50 w/w% NaOH, 100 grams, 1.25 mole), a 61.00 grams slurry of recycled
25 Raney copper (Mo promoted, 50 cc, 12.38 grams copper), a 10.29 gram slurry of fresh Raney copper (20 ppm Mo promoted, 10 cc, 0.33 grams copper), an added amount of sodium chlorate to simulate that found in various grades of NaOH, and 12.5 g deionized water. First cycle reaction mixtures were the same as above but with a 61.4 g slurry of fresh purge/replacement catalyst charges. The reactor is sealed and purged three times with nitrogen at 135 psig. The
30 reactor is then pressurized to 135 psig with nitrogen and warmed to 160-170°C over a period of about 30 minutes. Temperature is maintained at 160°C until the hydrogen evolution rate drops

WO 00/66539

PCT/US00/12023

- 12 -

below detection limit for the mass flow indicator (about 2 cc/min H₂). The reaction time is recorded between reaching 160°C and cessation of the reaction. Stirring is continued until the temperature of the reaction mixture falls below 80°C. For reactions run overnight, the reactor is allowed to cool to ambient temperature with the heating mantle in place and the following day the reaction mixture is warmed to 80-85°C to facilitate filtration. The catalyst is then separated from the reaction mixture by filtration through a medium glass frit. During filtration, the catalyst is kept covered with a layer of water to prevent oxidation of the catalyst surface. The catalyst cake is washed with sufficient deionized water to remove traces of reaction mixture and the filtrate is collected for an analysis.

Fresh catalyst was recycled in the production of disodium iminodiacetate from diethanolamine. Varying amounts of sodium chlorate were added to the reaction mixture. One molecule of sodium chlorate can generate at least 3 oxidized copper atoms. A minimum estimate of the oxidized copper concentration in the reaction mixture would therefore be about 2800 ppm, 3700 ppm, 7400 ppm, and 0 ppm, respectively. The results listed in Table 1.

Table 1, Glycine Production versus Sodium Chlorate Concentration

NaClO ₃ Added	NaClO ₃ in Rx mixture	Glycine (mole %)	Glycolate (mole %)	Formate (mole %)
0.39 g	1,580 ppm	1.84	1.25	0.55
0.51 g	2,070 ppm	2.4	1.28	0.86
1.02 g	4,140 ppm	3.78	2.49	1.92
0 g	0	0.96	0.25	0.02

The amounts of glycine byproduct found in the resulting product solutions were found to vary as a function of the amount of sodium chlorate added at the start of each reaction. The reaction yielded about 0.38 % glycine, as well as other byproducts, per 1000 ppm of oxidized copper added to the solution by the sodium chlorate.

Example 8

A series of tests essentially the same as described in Example 7 were run sequentially to determine the effect of repeated sequential exposure of catalyst to a reaction mixture containing varying amounts of oxidizing reagents. The amount of oxidized copper in the reaction mixture, presuming each molecule of oxidizing agent creates about 3 molecules of oxidized copper, is about 1800 ppm for cycles 2 and 3, about 360 ppm for cycle 6, about 900 ppm for cycle 7, and about 3600 for cycle 8.

WO 00/66539

PCT/US00/12023

- 13 -

The data is presented in Table 2. The reaction yielded about 0.31% glycine, as well as other byproducts, per 1000 ppm of oxidized copper added to the solution by the sodium chlorate.

The amount of selectivity lost due to reuse of catalyst is small relative to the loss of selectivity due to oxidizing reagents. The presence of oxidizing agents appears to have little
5 effect on the long term degradation of catalyst.

Table 2, Glycine Production versus Sodium Chlorate Concentration in Sequential Runs

	Cycle	NaClO ₃ added, g	NaClO ₃ Rx mixture	Glycine	Corrected*	Glycolate	Formate
10	1	0	0	0.74	0.74	0.3	-
	2	0.25	1000 ppm	1.81	1.75	1.52	0.42
	3	0.25	1000 ppm	1.89	1.77	1.16	0.43
	4	0	0	0.94	0.76	0.48	0.27
	5	0	0	0.96	0.72	0.38	-
15	6	0.05	200 ppm	1.28	0.98	0.46	-
	7	0.125	510 ppm	1.62	1.26	0.53	-
	8	0.5	2030 ppm	2.4	1.98	0.83	0.52
	9	0	0	1.14	0.66	0.37	-

*corrected glycine concentration for a use related increase of 0.06 mole %/recycle

20 Although the invention has been described in terms of specified embodiments which are set forth in considerable detail, it should be understood that this is by way of illustration only since alternative embodiments and operating techniques will become apparent to those skilled in the art in view of the disclosure. For example, there are numerous methods of reducing oxidized copper in addition to simply excluding gaseous air from the reactor. Accordingly, modifications
25 can be made and other techniques used without departing from the spirit of the described invention.

WO 00/66539

PCT/US00/12023

- 14 -

Claims:

1. A process of manufacturing an amino carboxylic acid salt comprising
 - a) contacting an aqueous solution of a primary aminoalcohol with a strong hydroxide base in the presence of an effective amount of a metallic copper containing catalyst to form a reaction mixture within a reactor, wherein the reaction mixture
5 contains less than about 3000 ppm of oxidized copper; and
 - b) reacting the mixture to convert the primary alcohol to a carboxylic acid salt.
2. The process of claim 1 wherein the mixture contains less than about 500 ppm of oxidized copper.
3. The process of claim 1 wherein the mixture contains less than about 100 ppm of oxidized
10 copper.
4. The process of claim 1 wherein the mixture contains less than about 50 ppm of oxidized copper.
5. The process of claim 1 wherein the catalyst comprises a hydroxide-resistant support, an anchor metal deposited on the support, and an element selected from the group consisting of
15 copper, cobalt, nickel, cadmium and mixtures thereof on or combined with the anchor metal.
6. The process of claim 1 wherein the catalyst comprises Raney copper.
7. The process of claim 1 wherein the catalyst comprises Raney copper and also comprises one or more of chromium, titanium, niobium, tantalum, zirconium, vanadium, molybdenum, manganese, tungsten, cobalt, and nickel.
- 20 8. The process of claim 1 wherein the concentration of dissolved molecular oxygen in the reactor mixture is less than about 5 ppm.
9. The process of claim 1 wherein the concentration of dissolved molecular oxygen in the reactor mixture is less than about 1 ppm.
10. The process of claim 1 wherein the concentration of dissolved molecular oxygen in the
25 reactor mixture is less than about 0.5 ppm.

WO 00/66539

PCT/US00/12023

- 15 -

11. The process of claim 1 further comprising removing molecular oxygen-containing gas from the reactor.
12. The process of claim 11 wherein air is removed from the reactor by displacement with fluids, by displacement with another gas, by vacuum, or by a combination thereof.
- 5 13. The process of claim 1 wherein the reactor mixture comprises between about 5 ppm to about 50 ppm of an oxygen sequestering agent.
14. The process of claim 13 wherein the oxygen sequestering agent is hydrogen sodium sulfite.
15. The process of claim 1 wherein the reactor mixture comprises less than about 1000 ppm
10 of chlorite, chlorate, perchlorate, and hypochlorite salts.
16. The process of claim 1 wherein the mixture comprises less than about 500 ppm of chlorite, chlorate, perchlorate, and hypochlorite salts.
17. The process of claim 1 wherein the mixture comprises less than about 200 ppm of chlorite, chlorate, perchlorate, and hypochlorite salts.
- 15 18. The process of claim 1 wherein the mixture comprises less than about 40 ppm of chlorite, chlorate, perchlorate, and hypochlorite salts.
19. The process of claim 1 wherein the strong hydroxide base comprises less than about 500 ppm of chlorite, chlorate, perchlorate, and hypochlorite salts.
20. The process of claim 1 wherein the strong hydroxide base comprises less than about 200
20 ppm of chlorite, chlorate, perchlorate, and hypochlorite salts.
21. The process of claim 1 wherein the strong hydroxide base comprises less than about 40 ppm of chlorite, chlorate, perchlorate, and hypochlorite salts.
22. The process of claim 1 further comprising exposing the catalyst to acid prior to contacting the catalyst with the strong hydroxide base and primary aminoalcohol.

WO 00/66539

PCT/US00/12023

- 16 -

23. The process of claim 22 wherein the acid comprises organic acid, inorganic acid, EDTA, or mixtures thereof.
24. The process of claim 1 further comprising exposing the catalyst to a reducing agent prior to contacting the catalyst with the strong hydroxide base and primary aminoalcohol.
- 5 25. The process of claim 24 wherein the reducing agent comprises one or more of sodium borohydride, formaldehyde, hydrazine, hydrogen, formic acid or salt thereof prior to contacting the catalyst with the strong hydroxide base and primary aminoalcohol.
26. The process of 24 wherein the reducing agent comprises formic acid or salt thereof.
27. The process of claim 1 further comprising removing oxidized copper from the aqueous
10 solution comprising the strong hydroxide base with ion exchange resins.
29. The process of claim 1 wherein the aminoalcohol is diethanolamine, the strong hydroxide base is sodium hydroxide, the catalyst comprises Raney copper, and the amino carboxylic acid salt product is disodium iminodiacetate.
30. The process of claim 29 wherein the concentration of oxidized copper in the reaction
15 mixture prior to reacting the mixture is below about 50 ppm.
31. The process of claim 1 wherein the concentration of oxidized copper in the catalyst prior to reacting the mixture is below about 500 ppm.
32. The process of claim 1 wherein the concentration of oxidized copper in the catalyst prior to reacting the mixture is below about 100 ppm.
- 20 33. The process of claim 1 wherein the concentration of oxidized copper in the catalyst prior to reacting the mixture is below about 40 ppm.
34. A process for producing an aminocarboxylic acid salt from an aminoalcohol, said process comprising contacting the aminoalcohol with a strong hydroxide base, a copper-containing catalyst, and water, which process is characterized by conducting the reaction while maintaining
25 the oxidized copper concentration in the reaction mixture at 100 ppm or less.

WO 00/66539

PCT/US00/12023

- 17 -

35. The process of claim 34 wherein the oxidized copper concentration in the reaction mixture is maintained at 50 ppm or less.

INTERNATIONAL SEARCH REPORT

In. ational Application No PCT/US 00/12023		
A. CLASSIFICATION OF SUBJECT MATTER IPC 7 C07C227/02 C07C229/16		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 C07C		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal, WPI Data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 220 054 A (GOTO TAKAKIYO ET AL) 15 June 1993 (1993-06-15) cited in the application examples 16,17	1-35
X	US 5 220 055 A (GOTO TAKAKIYO ET AL) 15 June 1993 (1993-06-15) examples 5-7	1-35
X	DATABASE WPI Section Ch, Week 199733 Derwent Publications Ltd., London, GB; Class 805, AN 1997-359115 XP002147403 & JP 09 151168 A (KAWAKEN FINE CHEM CO LTD), 10 June 1997 (1997-06-10) abstract	1-35
-/-		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C.		<input checked="" type="checkbox"/> Patent family members are listed in annex.
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p>		
Date of the actual completion of the international search 14 September 2000		Date of mailing of the international search report 28/09/2000
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2220 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 upo nl, Fax: (+31-70) 340-3018		Authorized officer Pauwels, G

Form PCT/ISA/210 (second sheet) (July 1992)

page 1 of 2

INTERNATIONAL SEARCH REPORT

In. ational Application No
PCT/US 00/12023

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 504 381 A (ERCROS SA) 23 September 1992 (1992-09-23) example 1	1-35
X	US 4 782 183 A (GOTO TAKAKIYO ET AL) 1 November 1988 (1988-11-01) examples	1-35
P, X	EP 0 945 428 A (FINCHIMICA SRL) 29 September 1999 (1999-09-29) claims; examples	1-35

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

page 2 of 2

INTERNATIONAL SEARCH REPORT

Information on patent family members

II. International Application No.

PCT/US 00/12023

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5220054 A	15-06-1993	AU 634918 B	04-03-1993
		AU 8913091 A	25-06-1992
		CA 2074486 A	28-05-1992
		DE 69120660 D	08-08-1996
		DE 69120660 T	31-10-1996
		DK 513396 T	29-07-1996
		EP 0513396 A	19-11-1992
		ES 2089493 T	01-10-1996
		WO 9209559 A	11-06-1992
		JP 2939335 B	25-08-1999
		KR 9709569 B	14-06-1997
		MX 9102823 A	01-06-1992
		JP 2968104 B	25-10-1999
		JP 4342549 A	30-11-1992
US 5220055 A	15-06-1993	AU 636803 B	06-05-1993
		AU 8711791 A	20-05-1992
		CA 2071999 A,C	24-04-1992
		DE 69115883 D	08-02-1996
		DE 69115883 T	05-06-1996
		DK 506973 T	29-01-1996
		EP 0506973 A	07-10-1992
		ES 2081497 T	01-03-1996
		WO 9206949 A	30-04-1992
		JP 2916256 B	05-07-1999
		KR 9506892 B	26-06-1995
		MX 9101721 A	05-06-1992
JP 9151168 A	10-06-1997	NONE	
EP 0504381 A	23-09-1992	ES 2031412 A	01-12-1992
		BR 9105914 A	10-11-1992
		DE 69110447 D	20-07-1995
		DE 69110447 T	25-01-1996
		HK 1007139 A	01-04-1999
		JP 7047125 B	24-05-1995
		JP 5500475 T	04-02-1993
		AT 123760 T	15-06-1995
		AU 634103 B	11-02-1993
		AU 8666391 A	28-04-1992
		CA 2070176 A	05-04-1992
		DK 504381 T	30-10-1995
		WO 9206069 A	16-04-1992
		ES 2074732 T	16-09-1995
US 4782183 A	01-11-1988	JP 1053863 B	15-11-1989
		JP 1567316 C	10-07-1990
		JP 60078948 A	04-05-1985
		JP 1053864 B	15-11-1989
		JP 1567317 C	10-07-1990
		JP 60078949 A	04-05-1985
		JP 1053865 B	15-11-1989
		JP 1567318 C	10-07-1990
		JP 60097945 A	31-05-1985
		JP 1053866 B	15-11-1989
		JP 1567319 C	10-07-1990
		JP 60100545 A	04-06-1985
		GB 2148287 A,B	30-05-1985

Form PCT/ISA/210 (patent family annex) (July 1992)

page 1 of 2

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/12023

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0945428 A	29-09-1999	IT T0980249 A	23-09-1999
		AU 2127899 A	07-10-1999
		BR 9901155 A	11-01-2000

Form PCT/ISA/210 (patent family annex) (July 1992)

page 2 of 2